

REMARKS

Claims 1 through 23 are in this application and are presented for consideration. Claims 1 through 22 have been amended and new claim 23 has been added. The amended claims present the same subject matter as the original claims but have been amended to adapt them to the U. S. style. New claim 23 is similar to claim 3 but depends on claim 2.

The specification and claims have been amended in order to place this application in better form. The reference to claims in the specification has been deleted or amended. Appropriate headings have been added. No new matter has been added.

Favorable action on the merits is respectfully requested.

Respectfully submitted
for Applicant,

By: _____

John James McGlew

Registration No. 31,903

McGLEW AND TUTTLE, P.C.

JJM:jj
72093.1

Enclosed: Substitute Specification and Marked up copy of Translation


DATED: January 19, 2006
SCARBOROUGH STATION
SCARBOROUGH, NEW YORK 10510-0827
(914) 941-5600

SHOULD ANY OTHER FEE BE REQUIRED, THE PATENT AND TRADEMARK OFFICE
IS HEREBY REQUESTED TO CHARGE SUCH FEE TO OUR DEPOSIT ACCOUNT 13-
0410.

I HEREBY CERTIFY THAT THIS CORRESPONDENCE IS BEING DEPOSITED WITH
THE UNITED STATES POSTAL SERVICE AS EXPRESS MAIL IN AN ENVELOPE
ADDRESSED TO: COMMISSIONER OF PATENTS AND TRADEMARKS,
WASHINGTON, D.C. 20231, NO.: EV435294164US

McGLEW AND TUTTLE, P.C.

SCARBOROUGH STATION, SCARBOROUGH, NY 10510-9227

BY:  DATE: January 19, 2006

WO 2005/009667 — PT/EP2004/008104

SPECIFICATION

Process and Device for the Laser Machining
of Workpieces

Docket #72093

PROCESS AND DEVICE FOR THE LASER MACHINING
OF WORKPIECES

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This application is a United States National Phase application of International
Application PCT/EP2004/008104 filed July 20, 2004 and claims the benefit of priority under 35
U.S.C. § 119 of German Patent Application DE 103 33 456.4 filed July 22, 2003, the entire
5 contents of which are incorporated herein by reference.

FIELD OF THE INVENTION

[0002] The present invention pertains to a process and a device for the laser machining of workpieces with the features in the preamble of the principal claim.

BACKGROUND OF THE INVENTION

[0003] It is known from practice that different types of machining of a workpiece, e.g., welding, cutting, engraving, heating or the like, can be carried out with a laser tool. The laser tools are moved in relation to the workpiece by means of multiaxial mechanical manipulators, e.g., compound tables, multiaxial articulated-arm robots or the like. During laser welding, the laser tool is usually guided by means of a pressing element in contact with and at a constant distance from the workpiece. Focusing optical systems with fixed and relatively short focal distances may be used here. Furthermore, laser remote welding, in which a laser with fixed and longer focal distance is guided by a multiaxial manipulator at a greater distance in relation to the workpiece, is known in practice. In addition, it is known in remote welding that the laser tool may be equipped with a scanning means, which deflects the laser beam and moves it in relation to the workpiece.

[0004] The process velocity of the laser beam at the workpiece, e.g., the velocity of welding, is limited in the above-mentioned laser machining operations. It is approx. 4-6 m/minute in case of YAG or CO₂ lasers. Higher velocities of up to approx. 10 m/minute can be reached at present with fiber lasers or disk lasers. The velocity of displacement, with which the

manipulator moves the laser tool along a predetermined path during machining, e.g., during laser welding, corresponds to the above-mentioned machining velocity. If machining operations are carried out stroke by stroke, e.g., during stitch seam welding, the manipulator can be moved faster during the transport phases between the welding operations. In most machining operations, e.g., laser welding, it is desirable to place as many weld seams as possible in the shortest possible time. However, these efforts are limited by the relatively low velocity of welding, especially because the manipulator must perform acceleration and deceleration operations with its axes during the transport phases and the velocity level is also limited hereby. Moreover, such acceleration and deceleration operations lead to higher mechanical loads on the manipulator.

SUMMARY OF THE INVENTION

[0005] The object of the present invention is to ~~show~~provide a better and higher-performance laser machining technique.

~~This object is accomplished by the present invention with the features in the principal process claim and the principal device claim.~~

[0006] According to the invention, a process for machining workpieces is provided with a moving laser beam. The laser beam is held by a multiaxial mechanical manipulator at a manipulator hand at a spaced location above the workpiece and moved along a predetermined path during a displacing motion. At least partially oppositely directed compensating motion of

the laser beam is superimposed to the displacing motion during the machining operation.

[0007] The superimposition of the leading displacing motion and a compensating motion of the laser beam, which is in the opposite direction, has the advantage that the overall velocity level of the manipulator can be increased without the permissible machining velocity on the workpiece being exceeded. Due to the increase in output, more machining operations can be carried out in a shorter time than before. This has special advantages in case of laser welding and especially in case of stitch seams.

[0008] In particular, it is possible with the laser machining technique being claimed to join body parts by means of seam stitches especially rapidly and with high and settable strength or dimensional stability and to quasi "sew" a body similarly to a piece of clothing. This may happen both in case of geometry welding and deposit welding, in which both welding operations can take place in the same station and can pass over into one another. The separation into geometry welding or tacking in a framing station and a subsequent respot welding in downstream stations, which separation is common in spot welding, is no longer necessary, but it may nevertheless take place when desired.

[0009] Another advantage is the possibility of making the displacing motions uniform. If the velocity of displacement is sufficiently high, the displacing motion may be essentially

continuous, which relieves the manipulator. However, it is nevertheless possible here to increase the velocity during the transport phases in order to further increase the output.

[0010] The compensating motion is performed in one variant by means of a pivoting motion of the manipulator hand about one of its hand axes. Such a motion can be carried out rapidly and controlled very accurately, and this hand axis is preferably independent and can be controlled independently from the displacing motion of the other manipulator axes. The motion of a hand axis motion (along a hand axis) and especially along an axis located as far away on the driven side as possible has the further advantage that the masses involved can be kept low, which permits a low-inertia compensating motion.

[0011] The laser tool may be mounted by means of an extension arm or according to another suitable technique at a spaced location from or at an angular position in relation to the manipulator hand and the hand axis that is acted on for the compensating motion. Due to the increase in distance, small angles of rotation of the hand axis are sufficient to obtain great compensating motions and compensation paths. The transmission ratio or the leverage can be changed by changing the distance. The laser tool may have a short and preferably fixed focal distance depending on the type of the extension arm. This has advantages in terms of the focus tolerance and the broad selection of laser systems that can be used. As an alternative, it is possible to use laser optical systems with a long focal distance.

[0012] A scanning means is used to deflect the laser beam in the other variant. Even though this {scanning means} entails a greater design effort and higher costs than the variant described above, it offers the same technological advantages.

[0013] During a compensating pivoting motion, the laser beam is directed obliquely toward the workpiece in such a way that it gets ahead of the laser tool and the displacing motion at the beginning of the machining operation, especially at the beginning of the weld seam to be welded. Such a beam angle of, e.g., 15°, deviating from the normally perpendicular beam direction, has advantages during the entry of the laser beam into the workpiece. The direction of the beam changes in the course of the compensating motion over the perpendicular incidence angle up to an obliquely rearwardly directed beam angle, which in turn has advantages at the end of the seam.

~~Further advantageous embodiments of the present invention are described in the subclaims.~~

~~The present invention is schematically shown in the drawings as an example. Specifically,~~

~~Figure 1~~ shows

[0014] The various features of novelty which characterize the invention are pointed out with particularity in the claims annexed to and forming a part of this disclosure. For a better

understanding of the invention, its operating advantages and specific objects attained by its uses,
reference is made to the accompanying drawings and descriptive matter in which a preferred
embodiment of the invention is illustrated.

BRIEF DESCRIPTION OF THE DRAWINGS

5 **[0015]** In the drawings:

[0016] Figure 1 is a side view of a laser machining device with a multiaxial robot, an
extension arm and a laser tool at a workpiece;

;

[0017] Figure 2——~~shows~~is a motion process of a compensating motion of the laser
10 tool in seven steps A-G;

;

[0018] Figure 3——~~shows~~is a path view of the weld seam and the equivalent path;

[0019] Figure 4——~~shows~~is a velocity diagram for the displacement velocity, the
compensating velocity and the welding velocity;

15 ;

[0020] Figure 5——~~shows~~is a vector diagram of the superimposed velocities;

·
·
[0021] Figure 6——shows is different seam shapes;

·
·
[0022] Figure 7——shows is a welding diagram on a body side panel;·

5 [0023] Figure 8——shows is a side view of a variant of the laser machining device with
a differently arranged and directed extension arm;·

[0024] Figure 9——shows is an enlarged detail view of the extension arm with the
laser beam;· and

[0025] Figure 10——shows is another variant of the laser machining device with a
10 scanning means for deflecting the laser beam.

DESCRIPTION OF THE PREFERRED EMBODIMENT

[0026] Referring to the drawings in particular, Figures 1, 8 and 10 show different variants

of a laser machining device (1), which comprises at least one multiaxial mechanical manipulator (2) and a laser tool (3), which emits at least one laser beam (4) towards a workpiece (6).

[0027] The manipulator (2) is preferably designed as an at least six-axis articulated arm robot. In the embodiment being shown, it comprises a base (12), on which a bracket (11) is mounted rotatably about a first, vertical axis of rotation I, a rocker (10) being in turn mounted pivotably about a horizontal pivot axis II on the bracket (11). A robot arm (9) is mounted pivotably about another horizontal pivot axis III at the upper end of the rocker, and a three-axis robot hand (8) with three intersecting hand axes IV, V and VI being arranged at the front end of the robot arm (9). At the front end, the robot hand (8) has a rotatable driven flange (14), on which the laser tool (3) is mounted.

[0028] The laser tool (3) is shown only schematically in the drawings. It may be of any desired, suitable design, e.g., a YAG laser, a CO₂ laser, a fiber laser, a disk laser or the like. The laser light source (15) may be arranged externally, the laser beam being coupled at the laser tool (3) in a suitable manner via a line guide (16) with mirrors, optical fiber cables or the like.

Figures 8 and 10 show such an arrangement. In a variant of the embodiment being shown, the exiting laser beam (4) may be a multipart beam and consist of a plurality of individual beams split optionally by beam splitting.

[0029] The laser tool (3) is designed, e.g., as a laser welding head. It has a laser optical

system with a fixed focal distance, which may be approx. 150-400 mm, e.g., in the embodiment shown in Figures 1 through 4. For example, a longer, fixed focal distance of approx. 300-600 mm is used in the variant according to Figures 8 and 9.

[0030] Furthermore, the focal distance may vary depending on the type of the laser unit.

5 A YAG laser typically has a focal distance of, e.g., 240 mm. The focusing optical system has a fixed angle in the variants according to Figures 1 through 4 as well as Figures 8 and 9, so that the emitted laser beam (4) is not deflected. A scanning means (17) with pivotable mirrors, with which the laser beam (4) can be deflected, is used in the third embodiment according to Figure 10.

10 **[0031]** To compensate possible inaccuracies in focusing or positioning, the laser tool (3) may have a height compensation, with which the focusing optical system is adjusted in the direction of the beam in order to keep the focal spot and the focus on the surface of the workpiece (6). A corresponding distance-measuring means may be present for this purpose.

[0032] The workpiece (6) may be of any desired type. It is preferably one or more body
15 parts, especially bodyshell parts, of motor vehicles. Figure 5 shows an example for this with a body side panel. The workpiece (6) may comprise a plurality of components, which are

positioned in the correct position for joining and clamped by a clamping means (not shown). The workpiece (6) is preferably held stationarily, but it may alternatively also be moved in relation to the preferably stationary robot (2) or manipulator.

[0033] The laser tool (3) is arranged at a spaced location from the robot hand (8) in the variants shown in Figures 1 through 4 as well as Figures 8 and 9 and is spaced, e.g., by a corresponding extension arm (5). As an alternative, the laser tool (3) may have a correspondingly extended and optionally bent housing. In the embodiment shown in Figures 1 through 4, the extension arm (5) is longer than in the embodiment according to Figures 8 and 9, the focal distance ratios changing inversely.

[0034] Furthermore, it is possible to do away with an extension arm (5) and to arrange a laser tool (3) with a correspondingly longer focal distance of, e.g., 600-1,500 mm directly on the driven flange (14).

[0035] In the embodiment according to Figures 1 through 4 with a stationary workpiece (6), the laser tool (3) and the extension arm (5) are mounted flatly on the driven flange (14) of the robot hand, (8), so that the driven axis VI of the robot hand (8) and the axis in which the laser beam (4) exits coincide. As an alternative, the robot hand (8) may be rotated downwards or upwards by approx. 90° about the transverse hand axis V according to Figures 8 and 9, the extension arm (5) being arranged at right angles at the driven flange (14) and at right angles in

relation to the driven axis VI.

[0036] There is a free working distance \underline{a} between the lower or front end of the laser tool (3) and the workpiece (6). The focal distance \underline{b} of the focusing optical system, which is arranged in the laser tool (3) and is not shown in greater detail, is essentially equal or somewhat greater.

5 The tool center point coordinate (TCP coordinate) in the direction of the tool or the laser beam is designated by \underline{x} . It relates to a flange system of coordinates, which is arranged preferably in the center of the driven flange (14) and is used as the reference for the displacing and compensating motions explained below as well as for the orientations of the laser beam (4) and of the laser tool (3). The TCP coordinate \underline{x} is preferably the distance between the focus and the low end of the
10 flange system of coordinates.

[0037] In all variants, the robot (2) holds the laser tool (3) at a preferably constant distance \underline{a} from the workpiece (6) and guides same along a preprogrammed path, which is preferably stored in the robot control (13), along the surface of the workpiece. There preferably is no contact between the laser tool (3) and the workpiece (6). This global guide motion is called
15 displacing motion, the robot with the robot hand (8) and especially with the driven flange (14) performing a displacement path \underline{f} and $\{at\}$ a displacement velocity $\underline{V_r}$ along the path (not shown) at the workpiece (6) due to the motion of its axes. The laser tool (3) would normally be moved and guided within the framework of this displacing motion such that the exiting laser beam (4) is

directed at right angles to the surface of the workpiece.

[0038]_____Any greatly varying machining operations can be performed with the laser tool (3). A welding process is carried out in the preferred exemplary embodiment. The machining operations are preferably interrupted or intermittent, while, e.g., stitch seams are placed, which consist of a plurality of short seams or seam sections (7), which are placed at any distance from one another one after another in the direction of the path. Figure 4 illustrates in the upper part such a stitch seam. During stitch seam welding, the robot (8) ~~[sic - Tr.Ed. (2)]~~ performs transport motions, during which the laser beam (4) is switched off, between the individual seams (7). This may be carried out in any desired and suitable manner by switching off the laser beam source, but, as an alternative, also by temporarily switching the laser beam by means of a shunt over to other laser tools. The seam lengths, seam shapes and the transport paths may vary.

[0039]_____An at least partially oppositely directed compensating motion of the laser beam (4) is superimposed during the welding of the stitch seam during the welding phases during which the displacing motion of the robot (2) is performed. The velocity of displacement $\underline{V_r}$ is greater here than the compensation velocity $\underline{V_w}$ directed in the opposite direction. For example, the machining or welding velocity $\underline{V_s}$ of the laser beam (4) acting on the workpiece (6) is reduced as a result and it is substantially lower than the velocity of displacement $\underline{V_r}$. A restoring motion may take place between the welding phases in order to return the laser beam into the

starting position before or at the beginning of the next welding phase.

[0040] As an alternative, the compensating velocity V_w directed in the opposite direction may be greater, at least in some areas, than the velocity of displacement V_r , which even generates a rearwardly directed machining or welding velocity V_s . As a result, it is possible, e.g., to
5 prepare layers of scales during welding by a pendular motion of the laser beam (4), which motion is directed alternately forward and backward. In addition, the laser beam (4) may be deflected laterally during the compensating motion.

[0041] Figure 6 shows different seam shapes that can be prepared by the technique being claimed. In the simplest and preferred embodiment variant, the stitch seam consists of
10 individually and essentially straight or singly bent seam sections (7). This is shown in the upper part of Figure 6. The lower part of Figure 6 shows other variants. These may be, on the one hand, zigzag seam shapes deflected at right angles to the direction of the path. Besides these finite seam shapes, these may also be endless seam shapes, e.g., circles, ovals or spiral shapes according to Figure 6. The preferred exemplary embodiment of stitch seams consisting of
15 straight seam lines will be discussed in the following explanations. Corresponding modifications apply to the other seam shapes shown in Figure 6.

[0042]_____ The compensating motion of the laser beam (4) is preferably an angular motion, which takes place at least partially, i.e., with one motion component, in the direction of the path being followed and opposite the displacing motion. The lateral deflecting motion mentioned may be possible as well. The compensating motion of the laser beam (4) is performed in the
5 embodiments according to Figures 1 through 4 and Figures 8 and 9 by a pivoting motion of the robot hand (8) about at least one of its hand axes IV, V, VI.

[0043]_____ In the exemplary embodiment shown in Figure 1 with the straight stitch seam on an upright workpiece (6), the likewise upright robot (2) performs a displacement motion $\underline{V_r}$ with its axes I through IV, which said motion is directed essentially in parallel to the workpiece (6).

10 The compensating motion takes place by rotation of the driven flange (14), the extension arm (5) and the laser tool (3) about the transversely extending hand axis V. The arrows $\underline{V_r}$ and $\underline{V_w}$ illustrate the displacing and compensating motion. A possible lateral deflecting motion may take place, e.g., with the robot hand (8) pivoted upwardly or downwardly by 90° by a possibly superimposed rotation of the flange axis VI.

15 **[0044]**_____ In the variant according to Figures 8 and 9, corresponding displacing and compensating motions are performed on a horizontal workpiece (6) by the travel motion of the robot (2) with the axes I through IV and the rotation about the hand axis V.

[0045]_____The hand axis responsible for the compensating motion, here the axis V, can be controlled independently from the displacing motion. This does not rule out that the hand axis in question participates in the displacing motion in order to guide the laser tool (3) along the surface of the workpiece and the desired path. However, the compensating pivoting motion can be
5 superimposed to this axis component of the displacing motion. It is useful for this purpose if the robot control (13) permits not only angle changes related to the path but can also be programmed in both a path-related and angle-related manner.

[0046]_____Due to the distance x of the TCP coordinates, small angular motions about the hand axis V lead to correspondingly long paths of the laser beam (4) on the workpiece (6). The
10 superimposed compensating motion, which is directed in the opposite direction, correspondingly leads to a reduction of the machining and welding velocity V_s on the workpiece (6).

[0047]_____Figure 2 illustrates such a motion process during the welding of a short seam section in seven steps A through G.

[0048]_____Step A shows the starting position at the end of a transport phase with the laser
15 beam (4) switched off. The laser beam axis or the orientation of the laser tool (3) and of the

extension arm (5) is directed at right angles to the surface of the workpiece.

[0049] _____ The compensating motion starts from this position, and the laser tool (3) is turned, before the beginning of welding, in the direction of the displacing motion indicated by an arrow V_r and is directed obliquely in relation to the surfaced of the workpiece. The laser beam (4), which is switched on thereafter, has a forwardly directed, oblique beam angle α , with which it reaches the surface of the workpiece (6), at the beginning of the weld seam according to Step B. At the beginning of welding, the point at which the laser beam (4) reaches the surface moves ahead of the laser tool (3) or the low end of the flange system of coordinates. This angle α has its maximum at the beginning of welding and may equal, depending on the type of the laser and other welding conditions explained in greater detail below, e.g., approx. 15° in relation to the vertical to the workpiece surface, which is drawn in broken line. Larger angles of, e.g., 60° , are also possible, depending on the application.

[0050] _____ The beam angle α is reduced in the further course of the displacing motion due to the continuously opposite compensating motion according to arrow V_w about the hand axis V. Figure C shows this with a halved, obliquely forwardly directed beam angle α' of approx. 7.5° . The beam angle of the laser beam is perpendicular to the workpiece surface in Figure D.

[0051]_____ An obliquely rearwardly directed beam angle β , β' , which progressively increases, is generated during the further displacing motion due to the continued compensating motion V_w . The rearward beam angle β' equals approx. 7.5° in Figure E.

[0052]_____ Figure F illustrates the end of the seam (7) and a maximum rearward beam angle β of approx. 15° . The point at which the laser beam (4) reaches the surface trails the laser tool (3) or the low end of the flange system of coordinates.

[0053]_____ The laser beam (4) is switched off at the end of the seam, and the laser tool (3) is subsequently turned in the direction of the displacing motion in a restoring motion during the transport phase and is directed at right angles to the workpiece surface. Figure G illustrates this position, which is also the starting position A for the next seam section and the next welding phase.

[0054]_____ The compensating motion preferably takes place symmetrically to the seam section (7), so that the absolute values of the respective beam angles α , α' , β , β' directed forward and backward are approximately equal. The restoring motion may likewise be uniform. The velocity of displacement V_r is preferably constant during welding. The compensating velocity V_w is preferably constant as well. A constant welding velocity V_s is obtained due to the superimposition. However, the size ratios and the relative ratios of the compensating and displacing motions and the respective velocities V_w and V_r thereof may vary if needed, and the velocity of welding, V_s , changes as well.

[0055]_____ Due to the rotating compensating motion, the focal point describes an arc. For compensating, either the robot (2) with its axes I through V may perform an arc-shaped displacing motion directly correspondingly in the opposite direction, so that the focal point always remains at a constant position in relation to the workpiece surface, ~~[the. The focal point]~~ may be on or just below the workpiece surface. As an alternative, compensation of the arc-shaped motion and a shift of focus, which is normally associated with it, may take place due to the above-mentioned height adjustment of the focusing means.

[0056]_____ As is illustrated in Figure 3, the traveled path of displacement \underline{f} of the flange system of coordinates is substantially greater during welding than the welding path or the seam length \underline{s} .

[0057]_____ Figure 4 illustrates the quantitative velocity ratios in a diagram, where seam sections (7) of the stitch seam and the forwardly and rearwardly directed beam angles occurring in the process are shown schematically in the top part.

[0058]_____ Figure 5 shows the superimposition of the velocity vectors \underline{V}_R , \underline{V}_W and \underline{V}_S , taking

into account the value and the direction thereof for the example of a straight stitch seam according to Figures 1 through 4.

[0059] During the welding and transport phases, the robot (2) may travel at a constant velocity of displacement \underline{V}_R , as it is indicated by a solid line in Figure 4. An exactly oppositely directed equalizing velocity \underline{V}_W of the focus on the workpiece surface, which is, e.g., likewise constant and half the velocity of displacement \underline{V}_R , is generated by the compensating motion. Due to the superimposition of the two velocities \underline{V}_R and \underline{V}_W directed in opposite directions according to Figure 5, a welding velocity \underline{V}_S of 5 m/minute is obtained, which corresponds, e.g., to the maximum possible process velocity. Other and higher welding and machining velocities can also be attained with laser tools (3) of improved quality or in other machining processes.

[0060] In a variant of the conditions shown in Figure 4, the velocity of displacement \underline{V}_R and the compensating velocity \underline{V}_W may not be constant and may be variable during the welding phase. This is necessary, e.g., to make it possible to prepare the different seam shapes shown in Figure 6.

[0061] The velocity of displacement \underline{V}_R corresponds to the velocity of welding \underline{V}_S in a conventional welding process. Thanks to the compensating motion and the increase in the distance \underline{x} , the velocity of displacement \underline{V}_R can be substantially increased, e.g., to threefold,

compared to the state of the art. In a variant of the above-described embodiment, it is also possible now to further increase the velocity of displacement V_r during the transport phases, which is illustrated by broken lines in Figure 4.

[0062]_____ Due to the overall increase in the velocity level of the velocity of displacement V_r ,

5 the welding robot can cover the distances between the weld seam sections much more rapidly than before and place more weld seams or seam sections than before during the same time.

Figure 7 illustrates, e.g., such a process during the welding of a side panel of a vehicle body in a single rotary motion. All seam sections are prepared here by a single welding robot (2) according to Figure 1 in a circular path with a plurality of motion loops which may intersect each other.

10 **[0063]**_____ The vehicle body is quasi "sewn" with one or more stitch seams (7). The stitch seam (7) placed with optimal welding velocity and maximum output ensures high strength of the connection of the components that is appropriate for the stresses and can replace the hitherto separate tacking and the subsequent deposit welding and combine them in one welding operation in one station. The amount of heat introduced into the vehicle body is also limited by the

15 stitching and the seam interruptions.

[0064]_____ It is favorable for "sewing" to use a laser tool (3) with a high average or continuous wave output CW and high beam quality, e.g., a fiber laser. The seam shape can also be selected and set in a suitable manner in order to obtain the desired strength appropriate for the

stress. The laser tool (3) preferably has a pulse frequency that is variable but can preferably be set at a fixed value and maintained at a constant value during the process. The on and off times during the welding can be controlled and varied. The output of the laser tool (3) can be switched and modulated. It preferably has a frequency generator for this purpose, with which the pulse frequency and the output of the laser can be controlled and adapted to the materials of the components, the seam lengths and seam shapes. Furthermore, the laser beam may also be switched on and off for the stitch seam (7) with the transport and welding phases at the necessary frequency.

[0065]_____The possible weld seam lengths depend, among other things, on the TCP distance \underline{x} . The greater this distance \underline{x} , the greater is the maximum seam length \underline{s} .

[0066]_____Moreover, the weld seam length \underline{s} may also depend on the ratio of the velocity of displacement $\underline{V_r}$ to the maximum velocity of welding $\underline{V_s}$. The smaller the differences between $\underline{V_r}$ and $\underline{V_s}$, the greater may be the weld seam length \underline{s} . Conversely, short seam lengths \underline{s} make it possible to substantially increase the velocity of displacement $\underline{V_r}$ and consequently the overall output of the process.

[0067]_____The seam lengths \underline{s} depend, on the other hand, on the maximum possible oblique

beam angles α , β . These beam angles may vary depending on the material of the components and the type or the output of the laser tool (3). The greater these beam angles α , β , the greater the seam length s can be.

[0068]_____ In case of a corresponding focal distance x , the practically useful velocities of displacement V_r of the robot may be approx. 50 m/minute or higher at a welding velocity V_s of, e.g., 6 m/minute. The seam lengths s that are useful in practice are, e.g., in the range of 5 mm to 50 mm.

[0069]_____ Figures 8 and 9 show the variant mentioned in the introduction with the angular position of the extension arm (5) and of the laser tool (3). The extension arm (5) is fastened with a base plate to the driven flange (14) and projects obliquely rearwardly, so that the laser tool (3) mounted at the front end of the extension arm is offset rearwardly and downwardly in relation to the driven flange (14). The laser tool (3) is directed now such that the extension of the emitted laser beam (4) intersects the transversely located hand axis V at an intersection (18). This intersection (18) is preferably also the center of intersection of all three axes IV, V and VI.

[0070]_____ In this embodiment, the TCP coordinate x is the distance between the intersection (18) and the focal point on the workpiece surface (6). The robot (2) performs the displacement motion by a motion of its axes I-IV. The compensating motion takes place by a rotation of the robot hand (8), the extension arm (5) and the laser tool (3) about the hand axis V. The forwardly

and rearwardly directed beam angles α and β described in the exemplary embodiment shown in Figure 2 also develop now.

[0071] In the variant according to Figures 8 and 9, the extension arm (5) is shorter than in the first exemplary embodiment according to Figures 1-4. Depending on the desired working distance a , the focal distance b of the laser optical system may be equal to or greater than in the first exemplary embodiment.

[0072] Figure 10 illustrates the third variant, which was likewise mentioned above, in which the deflection of the laser beam (4) and the compensating motion are performed by a mobile scanning means (17). An extension arm (5) may be done away with in this case. The scanning means (17) is designed, e.g., as a scanner optical system with two or more rotatably movable mirrors, whose motion can be controlled from the robot control (13). Due to the rotations of the mirrors, the laser beam (4) can be deflected in one or two axes. The scanning means (17) is preferably accommodated in the housing of the laser tool (3), but it may alternatively also be arranged externally. The focusing optical system preferably has a fixed focal distance in this case as well.

[0073] Various modifications of the embodiments shown are possible. The position and the design of the workpiece (6) may vary, and the robot (2) varies its orientation accordingly. As

a result, it is also possible to process three-dimensional paths and seams, as in the case of the body (6) shown in Figure 7. The robot (2) now changes its orientation preferably such that only one and preferably the same hand axis will always be responsible for the compensating motion.

[0074]_____ It is possible in another variant to perform the compensating motion alternatively by a plurality of hand axes or by an attached rotating and/or linear unit. The rotating and/or linear unit will then move the laser tool (3) for the compensating motion independently from the robot hand (8). An extension arm (5) may possibly be done away with in this case.

[0075]_____ Furthermore, there are possibilities of variation in the case of the laser optical system, which may have, e.g., a variable focal distance. The laser optical system may otherwise be of any desired design.

[0076]_____ The embodiment of the manipulator (2) is also variable. In the simplest case, it may be a carriage device with a plurality of translatory axes, e.g., an x-y carriage. Mixed forms of rotatory and translatory axes and other numbers of axes and degrees of freedom are possible as well.

[0077]_____ Moreover, the type of the laser processes is also variable. This pertains, besides to welding, e.g., to cutting, surface machining, e.g., engraving, or specific surface heating.

~~LIST OF REFERENCE NUMBERS~~

- ~~1 Laser machining device~~
- ~~2 Manipulator, robot~~
- ~~3 Laser tool~~
- 5 ~~4 Laser beam~~
- ~~5 Extension arm~~
- ~~6 Workpiece~~
- ~~7 Seam~~
- ~~8 Manipulator hand, robot hand~~
- 10 ~~9 Manipulator arm, robot arm~~
- ~~10 Rocker~~
- ~~11 Bracket~~
- ~~12 Base~~
- ~~13 Robot control~~
- 15 ~~14 Driven flange~~
- ~~15 Laser source~~
- ~~16 Line~~
- ~~17 Scanning means, scanner optical system~~
- ~~18 Intersection, center of intersection~~
- 20 ~~a Free working distance~~

~~b — Focal distance of focusing optical system~~

~~x — TCP coordinate in direction of tool~~

~~V_r — Velocity of displacement of robot~~

~~V_s — Machining velocity, welding velocity~~

5 ~~V_w — Compensating velocity~~

~~f — Path of displacement of robot~~

~~s — Machining path, welding path, seam length~~

~~α — Beam angle forward~~

~~α — Beam angle forward~~

10 ~~β — Beam angle backward~~

~~β — Beam angle backward~~

[0078] While specific embodiments of the invention have been shown and described in detail to illustrate the application of the principles of the invention, it will be understood that the invention may be embodied otherwise without departing from such principles.

ABSTRACT OF THE DISCLOSURE

A method for machining workpieces (6) uses a moving laser beam (4), whereby the laser tool (3) is held at a separation above the workpiece (6) by means of a multi-axis mechanical manipulator (2) with a manipulator hand (8) and moved along a given track in an offset movement. During the machining process an at least partly opposing compensation movement of the laser beam (4) is superimposed on the offset movement. A device is provided for machining workpieces (6) with a moving laser beam (4). The laser tool (3) is held by means of a multi-axis mechanical manipulator (2) and a device for generation of a opposing compensation movement of the laser beam (4) is superimposed on the offset movement.